

19-May-2009 13:07:42 (model G.0/G.0+)

INFORMATION THEREIN; AND (4) UPON COMPLETION OF THE NEED TO RETAIN THE DRAWING, OR UPON DEMAND, RETURN THE DRAWING, ALL COPIES THEREOF, AND ALL MATERIAL COPIED THEREFROM. COPIES THEREOF, AND ALL MATERIAL COPIED THEREFROM.	
AND AGREES THAT, EXCEPT AS AUTHORIZED IN WRITING BY INGERSOLL-RAND CO. IT WILL (1) NOT USE THE DRAWING OR ANY COPY THEREOF OR THE CONFIDENTIAL OR TRADE SECRET INFORMATION THEREIN; (2) NOT COPY THE DRAWING; (3) NOT DISCLOSE TO OTHERS EITHER THE DRAWING OR THE CONFIDENTIAL OR TRADE SECRET	
GIVEN TO THE RECEIVER IN CONFIDENCE. THE RECEIVER BY RECEPTION AND RETENTION OF THE DRAWING ACCEPTS THE DRAWING IN CONFIDENCE UNLESS OTHERWISE SPECIFIED: J.HUN	
THIS DRAWING CONTAINS CONFIDENTIAL AND TRADE SECRET	RRIS
AND OTHER APPLICABLE GOVERNMENT RESTRICTIONS OR REGULATIONS DRAWING CONFORMS TO	ANGLE PROJE
WARNING: THE EXPORT OR REEXPORT OF THIS DRAWING OR A PRODUCT PRODUCED DO NOT SCALE DRAWING BY THIS DRAWING IS SUBJECT TO U.S. EXPORT ADMINISTRATION REGULATIONS	\bigcirc

UNLESS OTHERWISE SPECIFIED PRINTED DOCUMENT IS UNCONTROLLED

2		1		
REVISIONS				
DESCRIPTION		DATE	DWN	APV
ORIGINAL RELEASE		2003MAR19	A.BHAGAWAN	M.STICKLAND
ALL LINES ARE NOW .25 INCH, ALL REFERENCE TO PART NUMBERS FOR COMPONENTS WERE REMOVED FROM DRA	WING		J.HUNT	M.STICKLAND
RETURN TO 3/8 INCH LINE FROM BLOWDO SOLENOID TO AIR INLET VALVE	OWN	2003DEC09	C.FRAZIER	J.JACOBS
ADD TUBING, TUBING ELBOW, STREE TEE	E	2004JAN26	C.FRAZIER	J.JACOBS
UPDATED PRESSURE SWITCH WAS 54767 UPDATE SHEET FORMAT	173	2005APR15	VIJAY	J.JACOBS
.37 TUBING FROM ELBOW TO TEE MALE R WAS .25 TUBING; ADDED ISO IN NOTES FOR CLARIFICATIOI	RUN Í	2008MAY12	S.DIETRICH W.SORAH	C.FRAZIER
SOLENOID 1/4 PORT WAS 1/2 PORT REMOVED REDUCER BUSHING QTY 2		2009MAY22	W.SORAH	C.FRAZIER
	REVISIONS DESCRIPTION ORIGINAL RELEASE ALL LINES ARE NOW .25 INCH, ALL REFERENCE TO PART NUMBERS FOR COMPONENTS WERE REMOVED FROM DRA RETURN TO 3/8 INCH LINE FROM BLOWDO SOLENOID TO AIR INLET VALVE ADD STREE ELBOW UNDER FILTER INDICA ADD TUBING, TUBING ELBOW, STREE TEE AND ADJUSTABLE VALVE FOR ANTI-RUMI FEATURE UPDATED PRESSURE SWITCH WAS 54767 UPDATE SHEET FORMAT REPLACED AIR INLET VALVE AND RESTRUCTURED CONNECTING COMPONE .37 TUBING FROM ELBOW TO TEE MALE R WAS .25 TUBING; ADDED ISO IN NOTES FOR CLARIFICATION ADDED ADAPTER TO MOISTURE SEPARA SOLENOID 1/4 PORT WAS 1/2 PORT	REVISIONS DESCRIPTION ORIGINAL RELEASE ALL LINES ARE NOW .25 INCH, ALL REFERENCE TO PART NUMBERS FOR COMPONENTS WERE REMOVED FROM DRAWING RETURN TO 3/8 INCH LINE FROM BLOWDOWN SOLENOID TO AIR INLET VALVE ADD STREE ELBOW UNDER FILTER INDICATOR ADD TUBING, TUBING ELBOW, STREE TEE AND ADJUSTABLE VALVE FOR ANTI-RUMBLE FEATURE UPDATED PRESSURE SWITCH WAS 54767173 UPDATE SHEET FORMAT REPLACED AIR INLET VALVE AND RESTRUCTURED CONNECTING COMPONENTS; .37 TUBING FROM ELBOW TO TEE MALE RUN WAS .25 TUBING; ADDED ISO IN NOTES FOR CLARIFICATION; ADDED ADAPTER TO MOISTURE SEPARATOR SOLENOID 1/4 PORT WAS 1/2 PORT	REVISIONSDESCRIPTIONDATEORIGINAL RELEASE2003MAR19ALL LINES ARE NOW .25 INCH, ALL REFERENCE TO PART NUMBERS FOR COMPONENTS WERE REMOVED FROM DRAWING2003MAY29RETURN TO 3/8 INCH LINE FROM BLOWDOWN SOLENOID TO AIR INLET VALVE2003DEC09ADD STREE ELBOW UNDER FILTER INDICATOR ADD TUBING, TUBING ELBOW, STREE TEE AND ADJUSTABLE VALVE FOR ANTI-RUMBLE FEATURE2004JAN26UPDATED PRESSURE SWITCH WAS 54767173 UPDATE SHEET FORMAT2005APR15REPLACED AIR INLET VALVE AND RESTRUCTURED CONNECTING COMPONENTS; .37 TUBING FROM ELBOW TO TEE MALE RUN WAS .25 TUBING; ADDED ISO IN NOTES FOR CLARIFICATION; ADDED ADAPTER TO MOISTURE SEPARATOR2008MAY12SOLENOID 1/4 PORT WAS 1/2 PORT2009MAY22	REVISIONSDESCRIPTIONDATEDWNORIGINAL RELEASE2003MAR19A.BHAGAWANALL LINES ARE NOW .25 INCH, ALL REFERENCE TO PART NUMBERS FOR COMPONENTS WERE REMOVED FROM DRAWING2003MAY29J.HUNTRETURN TO 3/8 INCH LINE FROM BLOWDOWN SOLENOID TO AIR INLET VALVE2003DEC09C.FRAZIERADD STREE ELBOW UNDER FILTER INDICATOR ADD TUBING, TUBING ELBOW, STREE TEE AND ADJUSTABLE VALVE FOR ANTI-RUMBLE FEATURE2004JAN26C.FRAZIERUPDATED PRESSURE SWITCH WAS 54767173 UPDATE SHEET FORMAT2005APR15VIJAYREPLACED AIR INLET VALVE AND RESTRUCTURED CONNECTING COMPONENTS; .37 TUBING FROM ELBOW TO TEE MALE RUN WAS .25 TUBING; ADDED ISO IN NOTES FOR CLARIFICATION; ADDED ISO IN NOTES FOR CLARIFICATION; ADDED ADAPTER TO MOISTURE SEPARATOR2009MAY22W.SORAH