

19-May-2009 13:10:05 (model F.0/F.0+)

UNLESS OTHERWISE SPECIFIED PRINTED DOCUMENT IS UNCONTROLLED

2			1			
REVISIONS						
	DESCRIPTION		DATE	DWN	APV	
33	ORIGINAL RELEASE		2003MAR19	A.BHAGAWAN	M.STICKLAND	
	ALL LINES ARE NOW .25 INCH, ALL REFERENCE TO PART NUMBERS FOR COMPONENTS WERE REMOVED FROM DRA	WING.	2003MAY29	J.HUNT	M.STICKLAND	
	RETURN TO 3/8 INCH LINE FROM BLOWDOWN SOLENOID TO AIR INLET VALVE		2003DEC09	C.FRAZIER	J.JACOBS	
	ADD STREE ELBOW UNDER FILTER INDICATOR ADD TUBING, TUBING ELBOW, STREE TEE AND ADJUSTABLE VALVE FOR ANTI-RUMBLE FEATURE		2004JUL26	C.FRAZIER	J.JACOBS	
	REPLACED AIR INLET VALVE AND RESTRUCTURED CONNECTING COMPONE .37 TUBING FROM ELBOW TO TEE MALE F WAS .25 TUBING; ADDED ISO IN NOTES FOR CLARIFICATION ADDED ADAPTER TO MOISTURE SEPARA UPDATED FORMAT	RUN Í	2008MAY12	S.DIETRICH W.SORAH	C.FRAZIER	
	SOLENOID 1/4 PORT WAS 1/2 PORT REMOVED REDUCER BUSHING QTY 2		2009MAY22	W.SORAH	C.FRAZIER	